

Automatic Stretch Wrapper



RT AUTOMATIC

Performance

- **Production speed:** 40 LPH
- **Rotation Speed:** 17 RPM

Load Capacity

- **Max Load Weight:** 4000 lbs.
- **Max Load Dimensions (L X W x H):** 54" X 48" X 82"
- **Min Load Dimensions (L X W X H):** 36" X 36" X 24"
- **Max Inward Load Position (with respect to the pallet):** -4"
- **Max Outward Load Position (with respect to the pallet):** 4"

Machine Structure

- **Frame Construction:** Formed Steel



Film Delivery System

- **Single Motor Stretch Carriage:** 150-300% (250% standard)
- **Dual Motor Stretch Carriage:** 100-400% (250% standard)
- **Standard Film Width:** 20" (30" optional)
- **Cube Technology:** Innovative technology that combines multi-level variable pre-stretch, multi-level variable containment force, pro-active corner compensation, and strategic film placement to successfully wrap loads & ensure that they reach your customer in as-made condition by maintaining proper wrapping standards.
- **Cut and Swipe System:** Pressing film onto the load (no welding system)
- **Clamp:** Pincher Style, Fixed position
- **Carriage up / down speed (min/max):** 3 - 18 FPM
- **Roping System:** Partial roping with fixed roller
- **Height Sensing:** Photocell
- **Film Threading:** Patented S-Pattern
- **Corner Compensation:** Cube 1
- **Film Thickness:** 50 gauge - 150 gauge

Layouts

